NSN 4330-01-010-5130

Fluid Filter - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4330-01-010-5130 |
|--|
| Mounting Type: |
| Inlet connection head side and outlet connection head side |
| Body Outside Diameter: |
| 4.530 inches |
| Body Height: |
| 18.120 inches |
| Filtration Rating In Microns: |
| 3.0 |
| Drop Pressure: |
| 10.0 pounds per square inch |
| Differential Pressure: |
| 225.0 pounds per square inch |
| Design Type: |
| Reusable |
| Tempurature Rating: |
| Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit |
| Features Provided: |
| By-pass valve and differential pressure indicator and drain plug |
| Filtering Element Quantity: |
| 1 |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch |
| First Intake Connection Type: |
| Threaded internal pipe head side |
| First Discharge Connection Relationship To Intake Connection: |
| Identical to first intake connection |
| First Intake Thread Series Designator: |
| Npt |
| First Intake Thread Size: |
| 1.000 inches |
| First Intake Thread Direction: |
| Right-hand |
| Filtering System For Which Designed: |
| Full flow |
| Material: |
| Steel sediment bowl |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon |
| Surface Treatment: |
| Cadmium sediment bowl |

Style Designator:

High pressure threaded body

NSN 4330-01-010-5130

Fluid Filter - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000