## NSN 4330-01-026-3443

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-026-3443

Mounting Type:
Bracket w/drilled hole line
Mounting Hole Diameter:
0.406 inches
Mounting Hole Quantity:
4
Body Length:
19.750 inches
Body Outside Diameter:
8.375 inches
Filtration Rating In Microns:
45.0
Distance Between Mounting Hole Centers:
1.750 inches
Design Type:
Reusable
Features Provided:
Drain cock
Bracket Quantity:
2
Filtering Element Quantity:
Filtering Element Quantity: 1
1
1 Maximum Operating Pressure:
1  Maximum Operating Pressure: 75.0 pounds per square inch
Maximum Operating Pressure: 75.0 pounds per square inch Filtering Media Design:
Maximum Operating Pressure: 75.0 pounds per square inch Filtering Media Design: Perforated single filtering media response
Maximum Operating Pressure: 75.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type:
Maximum Operating Pressure: 75.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type: Threaded external pipe bottom
Maximum Operating Pressure: 75.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type: Threaded external pipe bottom First Discharge Connection Relationship To Intake Connection:
Maximum Operating Pressure: 75.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type: Threaded external pipe bottom First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
Maximum Operating Pressure: 75.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type: Threaded external pipe bottom First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator:
Maximum Operating Pressure: 75.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type: Threaded external pipe bottom First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator: Npt
Maximum Operating Pressure: 75.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type: Threaded external pipe bottom First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator: Npt First Intake Thread Size:
Maximum Operating Pressure: 75.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type: Threaded external pipe bottom First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator: Npt First Intake Thread Size: 0.500 inches
Maximum Operating Pressure: 75.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type: Threaded external pipe bottom First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator: Npt First Intake Thread Size: 0.500 inches First Intake Thread Direction:
Maximum Operating Pressure: 75.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type: Threaded external pipe bottom First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator: Npt First Intake Thread Size: 0.500 inches First Intake Thread Direction: Right-hand
Maximum Operating Pressure: 75.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type: Threaded external pipe bottom First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator: Npt First Intake Thread Size: 0.500 inches First Intake Thread Direction: Right-hand Material:
Maximum Operating Pressure: 75.0 pounds per square inch Filtering Media Design: Perforated single filtering media response First Intake Connection Type: Threaded external pipe bottom First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator: Npt First Intake Thread Size: 0.500 inches First Intake Thread Direction: Right-hand Material: Cellulose filtering medium

--

## NSN 4330-01-026-3443

Fluid Filter - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A24000