
NSN 4330-01-040-1136

Fluid Filter - Page 1 of 2



Mounting Type:

Threaded hole top

Mounting Hole Quantity:

2

Body Outside Diameter:

5.000 inches

Body Height:

11.690 inches

Filtration Rating In Microns:

25.0

Drop Pressure:

32.0 pounds per square inch

Distance Between Mounting Hole Centers:

3.188 inches

Design Type:

Reusable

Tempurature Rating:

Between -40.0 degrees fahrenheit and 375.0 degrees fahrenheit

Features Provided:

By-pass valve and drain plug

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Unc

Maximum Operating Pressure:

100.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Threaded internal pipe head side

Mounting Facility Thread Size:

0.375 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Nptf

First Intake Thread Size:

1.500 inches

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow or partial flow



NSN 4330-01-040-1136

Fluid Filter - Page 2 of 2

Special Features: Spin-on type element Material: Steel body Media For Which Designed: Fuel/oil, hydrocarbon Style Designator: Unthreaded shell Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A24000

