## NSN 4330-01-043-1121

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-043-1121

View Online at https://aerobasegroup.com/nsn/4330-01-043-1121
Mounting Type:
Unthreaded hole head side
Mounting Hole Diameter:
0.270 inches
Mounting Hole Quantity:
2
Body Length:
4.900 inches
Body Outside Diameter:
2.900 inches
Body Height:
11.290 inches
Filtration Rating In Microns:
3.0 absolute
Drop Pressure:
38.5 pounds per square inch
Differential Pressure:
50.0 pounds per square inch
Distance Between Mounting Hole Centers:
3.120 inches
Design Type:
Reusable
Tempurature Rating:
Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit
Features Provided:
By-pass valve and differential pressure indicator and
Filtering Element Quantity:
1
Maximum Operating Pressure:
3000.0 pounds per square inch
Filtering Media Design:
Pleated single filtering media response
First Intake Connection Type:
Threaded internal tube head side
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Thread Series Designator:
Un
First Intake Thread Size:
1.062 inches

12

First Intake Thready Qty Per Inch (tpi):

## **NSN 4330-01-043-1121** Fluid Filter - Page 2 of 2



First Intake Thread Class:
2b
First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow or by-pass flow
Special Features:
Pop-up type indicator w/manual reset; ports per sae j514h
Material:
Aluminum bodyfiber synthetic filtering medium and resin synthetic filtering mediumrubber buna n sealaluminum sediment bowl
Media For Which Designed:
Fuel/oil, hydrocarbon
Surface Treatment:
Anodize sediment bowlanodize body
Style Designator:
High pressure threaded body
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A24000