NSN 4330-01-043-1121

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-043-1121

Mounting Type:

Unthreaded hole head side

Mounting Hole Diameter:

0.270 inches

Mounting Hole Quantity:

2

Body Length:

4.900 inches

Body Outside Diameter:

2.900 inches

Body Height:

11.290 inches

Filtration Rating In Microns:

3.0 absolute

Drop Pressure:

38.5 pounds per square inch

Differential Pressure:

50.0 pounds per square inch

Distance Between Mounting Hole Centers:

3.120 inches

Design Type:

Reusable

Tempurature Rating:

Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit

Features Provided:

By-pass valve and differential pressure indicator and

Filtering Element Quantity:

1

Maximum Operating Pressure:

3000.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Threaded internal tube head side

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Un

First Intake Thread Size:

1.062 inches

First Intake Thready Qty Per Inch (tpi):

12

NSN 4330-01-043-1121

Fluid Filter - Page 2 of 2



First Intake Thread Class: 2b **First Intake Thread Direction: Right-hand** Filtering System For Which Designed: Full flow or by-pass flow **Special Features:** Pop-up type indicator w/manual reset; ports per sae j514h Material: Aluminum bodyfiber synthetic filtering medium and resin synthetic filtering mediumrubber buna n sealaluminum sediment bowl Media For Which Designed: Fuel/oil, hydrocarbon Surface Treatment: Anodize sediment bowlanodize body **Style Designator:** High pressure threaded body Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A24000