

View Online at <https://aerobasegroup.com/nsn/4330-01-087-1584>

Mounting Type:

Inlet connection top and outlet connection top

Drop Pressure:

35.0 pounds per square inch

Differential Pressure:

200.0 pounds per square inch

Design Type:

Reusable

Unit Quantity:

2

Features Provided:

Differential pressure indicator and drain plug and switch-over valve

Filtering Element Quantity:

2

Maximum Operating Pressure:

3000.0 pounds per square inch

First Intake Connection Type:

Raised face flange top

Second Intake Connection Relationship To First Intake Connection:

Identical

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Flange Outside Diameter:

3.500 inches

First Intake Flange Shape Style:

Round w/threaded bolt holes

First Intake Flange Face Style:

Raised

First Intake Flange Thickness:

1.094 inches

First Intake Flange Raised Face Height:

0.126 inches

First Intake Flange Raised Face Diameter:

2.123 inches

Filtering System For Which Designed:

Full flow

Special Features:

Furnished w/mech. Pop-up differential pressure indicator

Material:

Rubber synthetic seal

Media For Which Designed:

Fuel/oil, hydrocarbon

Surface Treatment:

Anodize body and passivate body

Specification Data:

81349-mil-f-24402 government specification

Specification Or Standard:

2n type and bf class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000