## NSN 4330-01-104-3991

Fluid Filter Element - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4330-01-104-3991

Filtration Rating In Microns:  10.0  Flow Direction: Outside in  Drop Pressure: 120.0 pounds per square inch  Design Type: Nonreusable  Tempurature Rating: Between 92.0 degrees fahrenheit and 130.0 degrees fahrenheit  Bodylength: 6.000 inches  Filtering Media Design: Pleated single filtering media response  Material: Cotton duck filtering medium  Media For Which Designed:
Flow Direction: Outside in Drop Pressure: 120.0 pounds per square inch Design Type: Nonreusable Tempurature Rating: Between 92.0 degrees fahrenheit and 130.0 degrees fahrenheit Bodylength: 6.000 inches Filtering Media Design: Pleated single filtering media response Material: Cotton duck filtering medium Media For Which Designed:
Outside in  Drop Pressure:  120.0 pounds per square inch  Design Type:  Nonreusable  Tempurature Rating:  Between 92.0 degrees fahrenheit and 130.0 degrees fahrenheit  Bodylength:  6.000 inches  Filtering Media Design:  Pleated single filtering media response  Material:  Cotton duck filtering medium  Media For Which Designed:
Drop Pressure:  120.0 pounds per square inch  Design Type:  Nonreusable  Tempurature Rating:  Between 92.0 degrees fahrenheit and 130.0 degrees fahrenheit  Bodylength:  6.000 inches  Filtering Media Design:  Pleated single filtering media response  Material:  Cotton duck filtering medium  Media For Which Designed:
120.0 pounds per square inch  Design Type: Nonreusable  Tempurature Rating: Between 92.0 degrees fahrenheit and 130.0 degrees fahrenheit  Bodylength: 6.000 inches  Filtering Media Design: Pleated single filtering media response  Material: Cotton duck filtering medium  Media For Which Designed:
Design Type: Nonreusable Tempurature Rating: Between 92.0 degrees fahrenheit and 130.0 degrees fahrenheit Bodylength: 6.000 inches Filtering Media Design: Pleated single filtering media response Material: Cotton duck filtering medium Media For Which Designed:
Nonreusable  Tempurature Rating: Between 92.0 degrees fahrenheit and 130.0 degrees fahrenheit  Bodylength: 6.000 inches  Filtering Media Design: Pleated single filtering media response  Material: Cotton duck filtering medium  Media For Which Designed:
Tempurature Rating: Between 92.0 degrees fahrenheit and 130.0 degrees fahrenheit  Bodylength: 6.000 inches  Filtering Media Design: Pleated single filtering media response  Material: Cotton duck filtering medium  Media For Which Designed:
Between 92.0 degrees fahrenheit and 130.0 degrees fahrenheit  Bodylength: 6.000 inches  Filtering Media Design: Pleated single filtering media response  Material: Cotton duck filtering medium  Media For Which Designed:
Bodylength: 6.000 inches Filtering Media Design: Pleated single filtering media response Material: Cotton duck filtering medium Media For Which Designed:
6.000 inches  Filtering Media Design:  Pleated single filtering media response  Material:  Cotton duck filtering medium  Media For Which Designed:
Filtering Media Design: Pleated single filtering media response  Material: Cotton duck filtering medium  Media For Which Designed:
Pleated single filtering media response  Material:  Cotton duck filtering medium  Media For Which Designed:
Material: Cotton duck filtering medium Media For Which Designed:
Cotton duck filtering medium  Media For Which Designed:
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
Cylindrical w/out container
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A24000