NSN 4330-01-111-9270

Fluid Filter Assembly - Page 1 of 2



| - | |
|---|--|
| | View Online at https://aerobasegroup.com/nsn/4330-01-111-9270 |
| | Mounting Type: |
| | Inlet connection head side and outlet connection head side |
| | Differential Pressure: |
| | 2250.0 pounds per square inch |
| | Design Type: |
| | Reusable |
| | Tempurature Rating: |
| | Between -40.0 degrees fahrenheit and 107.0 degrees fahrenheit |
| | Unit Quantity: |
| | 2 |
| | Features Provided: |
| | Differential pressure indicator and drain plug and switch-over valve |
| | Filtering Element Quantity: |
| | 2 |
| | Maximum Operating Pressure: |
| | 750.0 pounds per square inch |
| | Filtering Media Design: |
| | Pleated single filtering media response |
| | First Intake Connection Type: |
| | Raised face flange head side |
| | First Discharge Connection Relationship To Intake Connection: |
| | Identical to first intake connection |
| | First Intake Flange Outside Diameter: |
| | 10.000 inches |
| | First Intake Flange Shape Style: |
| | Round w/unthreaded bolt holes |
| | First Intake Flange Face Style: |
| | Raised |
| | First Intake Flange Thickness: |
| | 1.250 inches |
| | First Intake Flange Raised Face Height: |
| | 0.062 inches |
| | First Intake Flange Raised Face Diameter: |
| | 6.188 inches |
| | Filtering System For Which Designed: |
| | Full flow |
| | Material: |
| | Stainless steel filtering medium |
| | Shelf Life: |
| | N/a |
| | |

--

Unit Of Measure:

NSN 4330-01-111-9270

Fluid Filter Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A24000