NSN 4330-01-143-4408

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-143-4408

Mounting Type:
Unthreaded hole side near top
Mounting Hole Diameter:
0.453 inches
Mounting Hole Quantity:
4
Body Outside Diameter:
7.000 inches
Body Height:
13.280 inches
Filtration Rating In Microns:
10.0
Drop Pressure:
3.0 pounds per square inch
Differential Pressure:
25.0 pounds per square inch
Distance Between Mounting Hole Centers:
3.250 inches
Design Type:
Reusable
Tempurature Rating:
Tempurature Rating: 250.0 degrees fahrenheit
250.0 degrees fahrenheit
250.0 degrees fahrenheit Filtering Element Quantity:
250.0 degrees fahrenheit Filtering Element Quantity: 1
250.0 degrees fahrenheit Filtering Element Quantity: 1 Maximum Operating Pressure:
250.0 degrees fahrenheit Filtering Element Quantity: 1 Maximum Operating Pressure: 400.0 pounds per square inch
250.0 degrees fahrenheit Filtering Element Quantity: 1 Maximum Operating Pressure: 400.0 pounds per square inch Filtering Media Design:
250.0 degrees fahrenheit Filtering Element Quantity: 1 Maximum Operating Pressure: 400.0 pounds per square inch Filtering Media Design: Pleated single filtering media response
250.0 degrees fahrenheit Filtering Element Quantity: 1 Maximum Operating Pressure: 400.0 pounds per square inch Filtering Media Design: Pleated single filtering media response First Intake Connection Type:
250.0 degrees fahrenheit Filtering Element Quantity: 1 Maximum Operating Pressure: 400.0 pounds per square inch Filtering Media Design: Pleated single filtering media response First Intake Connection Type: Threaded internal pipe side near top
250.0 degrees fahrenheit Filtering Element Quantity: 1 Maximum Operating Pressure: 400.0 pounds per square inch Filtering Media Design: Pleated single filtering media response First Intake Connection Type: Threaded internal pipe side near top First Discharge Connection Relationship To Intake Connection:
250.0 degrees fahrenheit Filtering Element Quantity: 1 Maximum Operating Pressure: 400.0 pounds per square inch Filtering Media Design: Pleated single filtering media response First Intake Connection Type: Threaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Not identical
250.0 degrees fahrenheit Filtering Element Quantity: 1 Maximum Operating Pressure: 400.0 pounds per square inch Filtering Media Design: Pleated single filtering media response First Intake Connection Type: Threaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Not identical First Discharge Connection Type:
250.0 degrees fahrenheit Filtering Element Quantity: 1 Maximum Operating Pressure: 400.0 pounds per square inch Filtering Media Design: Pleated single filtering media response First Intake Connection Type: Threaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Not identical First Discharge Connection Type: Threaded external pipe bottom
250.0 degrees fahrenheit Filtering Element Quantity: 1 Maximum Operating Pressure: 400.0 pounds per square inch Filtering Media Design: Pleated single filtering media response First Intake Connection Type: Threaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Not identical First Discharge Connection Type: Threaded external pipe bottom First Intake Thread Series Designator:
250.0 degrees fahrenheit Filtering Element Quantity: 1 Maximum Operating Pressure: 400.0 pounds per square inch Filtering Media Design: Pleated single filtering media response First Intake Connection Type: Threaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Not identical First Discharge Connection Type: Threaded external pipe bottom First Intake Thread Series Designator: Un
250.0 degrees fahrenheit Filtering Element Quantity: 1 Maximum Operating Pressure: 400.0 pounds per square inch Filtering Media Design: Pleated single filtering media response First Intake Connection Type: Threaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Not identical First Discharge Connection Type: Threaded external pipe bottom First Intake Thread Series Designator: Un First Discharge Thread Series Designator:
250.0 degrees fahrenheit Filtering Element Quantity: 1 Maximum Operating Pressure: 400.0 pounds per square inch Filtering Media Design: Pleated single filtering media response First Intake Connection Type: Threaded internal pipe side near top First Discharge Connection Relationship To Intake Connection: Not identical First Discharge Connection Type: Threaded external pipe bottom First Intake Thread Series Designator: Un First Discharge Thread Series Designator: Nptf

1.500 inches

NSN 4330-01-143-4408 Fluid Filter - Page 2 of 2

