NSN 4330-01-143-8064

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-143-8064

| Mounting Type: |
|---|
| Unthreaded hole head side |
| Mounting Hole Diameter: |
| 0.265 inches |
| Mounting Hole Quantity: |
| 2 |
| Body Outside Diameter: |
| 3.125 inches |
| Differential Pressure: |
| 20.0 pounds per square inch |
| Design Type: |
| Reusable |
| Filtering Element Quantity: |
| 1 |
| Maximum Operating Pressure: |
| 1500.0 pounds per square inch |
| Filtering Media Design: |
| Pleated single filtering media response |
| First Intake Connection Type: |
| Threaded internal tube head side |
| First Discharge Connection Relationship To Intake Connection: |
| Identical to first intake connection |
| First Intake Thread Series Designator: |
| Unf |
| First Intake Thread Size: |
| 0.750 inches |
| First Intake Thread Class: |
| 3b |
| First Intake Thread Direction: |
| Right-hand |
| Filtering System For Which Designed: |
| By-pass flow |
| Special Features: |
| Grumman; f10 aircraft |
| Material: |
| Rubber buna n seal |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon |
| Surface Treatment: |
| Anodize container/cartridge |
| Style Designator: |

High pressure threaded body

NSN 4330-01-143-8064

Fluid Filter - Page 2 of 2



| She | lf | Life: | |
|------|----|-------|--|
| Oile | •• | LIIV. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000