NSN 4330-01-144-5556

Fluid Filter - Page 1 of 2



Mounting Type:

Threaded hole top

Mounting Hole Quantity:

2

Body Length:

3.820 inches

Body Width:

1.880 inches

Body Height:

7.600 inches

Filtration Rating In Microns:

10.0

Drop Pressure:

7.25 pounds per square inch

Distance Between Mounting Hole Centers:

1.880 inches

Design Type:

Reusable

Tempurature Rating:

Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit

Features Provided:

Differential pressure indicator

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Unc

Maximum Operating Pressure:

100.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Threaded internal pipe head side

Mounting Facility Thread Size:

0.250 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

Distance From Bottom Of Body To Center Of Inlet:

6.760 inches

First Intake Thread Series Designator:

Npt

First Intake Thread Size:

0.750 inches



NSN 4330-01-144-5556

Fluid Filter - Page 2 of 2



First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

Spin-on type element; no bypass; pressure gauge on indicator port no. 3

Material:

Rubber buna n seal

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

Tee type (hydraulic)

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A24000