## NSN 4330-01-175-1317

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-175-1317

View Online at https://aerobasegroup.com/nsn/4330-01-175-1317
Mounting Type:
Unthreaded hole top
Mounting Hole Diameter:
0.250 inches
Mounting Hole Quantity:
2
Body Outside Diameter:
3.500 inches
Body Height:
7.000 inches
Filtration Rating In Microns:
5.0
Distance Between Mounting Hole Centers:
2.756 inches
Design Type:
Limited
Tempurature Rating:
Between -20.0 degrees fahrenheit and 165.0 degrees fahrenheit
Features Provided:
Air bleed valve
Filtering Element Quantity:
Filtering Element Quantity: 1
1
1 Maximum Operating Pressure:
1  Maximum Operating Pressure: 150.0 pounds per square inch
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type:
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side First Discharge Connection Relationship To Intake Connection:
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator:
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator: Nptf
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator: Nptf First Intake Thread Size:
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator: Nptf First Intake Thread Size: 0.250 inches
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator: Nptf First Intake Thread Size: 0.250 inches First Intake Thread Direction:
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator: Nptf First Intake Thread Size: 0.250 inches First Intake Thread Direction: Right-hand
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator: Nptf First Intake Thread Size: 0.250 inches First Intake Thread Direction: Right-hand Filtering System For Which Designed:
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator: Nptf First Intake Thread Size: 0.250 inches First Intake Thread Direction: Right-hand Filtering System For Which Designed: Full flow
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator: Nptf First Intake Thread Size: 0.250 inches First Intake Thread Direction: Right-hand Filtering System For Which Designed: Full flow Special Features:
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator: Nptf First Intake Thread Size: 0.250 inches First Intake Thread Direction: Right-hand Filtering System For Which Designed: Full flow Special Features: W/aluminum bowl guard

Air

## NSN 4330-01-175-1317

Fluid Filter - Page 2 of 2



Sty				

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000