

View Online at <https://aerobasegroup.com/nsn/4330-01-178-8620>

Body Length:

3.610 inches

Body Height:

5.430 inches

Filtration Rating In Microns:

65.0 absolute and 43.0

Drop Pressure:

2.5 pounds per square inch

Design Type:

Reusable

Filtering Element Quantity:

1

Maximum Operating Pressure:

780.0 pounds per square inch

First Intake Connection Type:

Threaded external tube center

First Discharge Connection Relationship To Intake Connection:

Not identical

First Discharge Connection Type:

Threaded external tube side near top

Distance From Bottom Of Body To Center Of Inlet:

2.170 inches

Second Discharge Connection Relationship To Preceding Connection:

Not identical

Err Default:

Err default

First Intake Thread Series Designator:

Unj

First Discharge Thread Series Designator:

Unj

Second Discharge Thread Series Designator:

Unjef

First Intake Thread Size:

0.813 inches

First Discharge Thread Size:

0.812 inches

Second Discharge Thread Size:

0.438 inches

First Intake Thread Qty Per Inch (tpi):

20

First Discharge Thread Qty Per Inch (tpi):

20

First Intake Thread Class:

3a

First Discharge Thread Class:

3a

Err Default:

Err default

First Intake Thread Direction:

Right-hand

Second Discharge Thread Direction:

Right-hand

First Discharge Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Material:

Stainless steel filtering medium

Media For Which Designed:

Water

Style Designator:

Diverted flow basket strainer w/threaded cover

Fsc Application Data:

Water injection, engine

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000