
NSN 4330-01-189-1801

Fluid Filter - Page 1 of 2



Mounting Type:

Threaded hole top

Mounting Hole Quantity:

2

Body Outside Diameter:

3.750 inches

Body Height:

7.310 inches

Filtration Rating In Microns:

10.0

Differential Pressure:

15.0 pounds per square inch

Distance Between Mounting Hole Centers:

1.500 inches

Design Type:

Reusable

Tempurature Rating:

Between -40.0 degrees fahrenheit and 300.0 degrees fahrenheit

Features Provided:

By-pass valve

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Unc

Maximum Operating Pressure:

150.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Threaded internal tube head side

Mounting Facility Thread Size:

0.250 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Unf

First Intake Thread Size:

0.750 inches

First Intake Thread Class:

3b

First Intake Thread Direction:

Right-hand



NSN 4330-01-189-1801

Fluid Filter - Page 2 of 2



Filtering System For Which Designed:

Full flow

Special Features:

Spin-on element style a14 w/ 1.000-12 unf-2a thd

Material:

Rubber buna n seal

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

Unthreaded shell

Supplementary Features:

Gage port facility plugged

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A24000