NSN 4330-01-190-0020

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-190-0020

| Filtration Rating In Microns: |
|---|
| 20.0 absolute and 5.0 |
| Drop Pressure: |
| 2.0 pounds per square inch |
| Design Type: |
| Reusable |
| Tempurature Rating: |
| Between -40.0 degrees fahrenheit and 250.0 degrees fahrenheit |
| Filtering Element Quantity: |
| 1 |
| Maximum Operating Pressure: |
| 180.0 pounds per square inch |
| First Intake Connection Type: |
| Threaded external tube end |
| First Discharge Connection Relationship To Intake Connection: |
| Not identical |
| First Discharge Connection Type: |
| Threaded external tube end |
| First Intake Thread Series Designator: |
| Unjs |
| First Discharge Thread Series Designator: |
| Unjs |
| First Intake Thread Size: |
| 1.578 inches |
| First Discharge Thread Size: |
| 1.250 inches |
| First Intake Thready Qty Per Inch (tpi): |
| 14 |
| First Discharge Thready Qty Per Inch (tpi): |
| 14 |
| First Intake Thread Class: |
| 3a |
| First Discharge Thread Class: |
| 3a |
| First Intake Thread Direction: |
| Right-hand |
| First Discharge Thread Direction: |
| Right-hand |
| Filtering System For Which Designed: |
| Full flow |
| Material: |

Stainless steel filtering medium

NSN 4330-01-190-0020

Fluid Filter - Page 2 of 2

Fiig: A24000



| Material Specification: |
|--|
| Ams5570 assn standard 3rd material response seal |
| Media For Which Designed: |
| Air |
| Surface Treatment: |
| Silver seal |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |