NSN 4330-01-190-2923

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-190-2923

Mounting Type:
Bracket w/drilled hole bottom
Mounting Hole Diameter:
0.375 inches
Mounting Hole Quantity:
4
Body Length:
7.000 inches
Body Height:
25.000 inches
Filtration Rating In Microns:
40.0
Differential Pressure:
450.0 pounds per square inch
Design Type:
Reusable
Features Provided:
By-pass valve and differential pressure indicator and drain plug
Bracket Quantity:
1
Filtering Element Quantity:
2
2 Maximum Operating Pressure:
· -
Maximum Operating Pressure:
Maximum Operating Pressure: 300.0 pounds per square inch
Maximum Operating Pressure: 300.0 pounds per square inch First Intake Connection Type:
Maximum Operating Pressure: 300.0 pounds per square inch First Intake Connection Type: Threaded internal pipe side
Maximum Operating Pressure: 300.0 pounds per square inch First Intake Connection Type: Threaded internal pipe side First Discharge Connection Relationship To Intake Connection:
Maximum Operating Pressure: 300.0 pounds per square inch First Intake Connection Type: Threaded internal pipe side First Discharge Connection Relationship To Intake Connection: Not identical
Maximum Operating Pressure: 300.0 pounds per square inch First Intake Connection Type: Threaded internal pipe side First Discharge Connection Relationship To Intake Connection: Not identical First Discharge Connection Type:
Maximum Operating Pressure: 300.0 pounds per square inch First Intake Connection Type: Threaded internal pipe side First Discharge Connection Relationship To Intake Connection: Not identical First Discharge Connection Type: Threaded internal pipe bottom
Maximum Operating Pressure: 300.0 pounds per square inch First Intake Connection Type: Threaded internal pipe side First Discharge Connection Relationship To Intake Connection: Not identical First Discharge Connection Type: Threaded internal pipe bottom First Intake Thread Series Designator:
Maximum Operating Pressure: 300.0 pounds per square inch First Intake Connection Type: Threaded internal pipe side First Discharge Connection Relationship To Intake Connection: Not identical First Discharge Connection Type: Threaded internal pipe bottom First Intake Thread Series Designator: Npt
Maximum Operating Pressure: 300.0 pounds per square inch First Intake Connection Type: Threaded internal pipe side First Discharge Connection Relationship To Intake Connection: Not identical First Discharge Connection Type: Threaded internal pipe bottom First Intake Thread Series Designator: Npt First Discharge Thread Series Designator:
Maximum Operating Pressure: 300.0 pounds per square inch First Intake Connection Type: Threaded internal pipe side First Discharge Connection Relationship To Intake Connection: Not identical First Discharge Connection Type: Threaded internal pipe bottom First Intake Thread Series Designator: Npt First Discharge Thread Series Designator: Npt
Maximum Operating Pressure: 300.0 pounds per square inch First Intake Connection Type: Threaded internal pipe side First Discharge Connection Relationship To Intake Connection: Not identical First Discharge Connection Type: Threaded internal pipe bottom First Intake Thread Series Designator: Npt First Discharge Thread Series Designator: Npt First Intake Thread Size:
Maximum Operating Pressure: 300.0 pounds per square inch First Intake Connection Type: Threaded internal pipe side First Discharge Connection Relationship To Intake Connection: Not identical First Discharge Connection Type: Threaded internal pipe bottom First Intake Thread Series Designator: Npt First Discharge Thread Series Designator: Npt First Intake Thread Size: 3.000 inches
Maximum Operating Pressure: 300.0 pounds per square inch First Intake Connection Type: Threaded internal pipe side First Discharge Connection Relationship To Intake Connection: Not identical First Discharge Connection Type: Threaded internal pipe bottom First Intake Thread Series Designator: Npt First Discharge Thread Series Designator: Npt First Intake Thread Size: 3.000 inches First Discharge Thread Size:
Maximum Operating Pressure: 300.0 pounds per square inch First Intake Connection Type: Threaded internal pipe side First Discharge Connection Relationship To Intake Connection: Not identical First Discharge Connection Type: Threaded internal pipe bottom First Intake Thread Series Designator: Npt First Discharge Thread Series Designator: Npt First Intake Thread Size: 3.000 inches First Discharge Thread Size: 4.000 inches

Right-hand

NSN 4330-01-190-2923

Fluid Filter - Page 2 of 2



Filtering System For Which Designed:
Full flow
Material:
Steel comp 1010 body
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
High pressure angle strainer w/bolted cover
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A24000