## NSN 4330-01-198-3043

Fluid Filter - Page 1 of 2



view Online at https://aerobasegroup.com/hsh/4550-01-196-5045
Mounting Type:
Unthreaded hole side near top
Mounting Hole Diameter:
0.438 inches
Mounting Hole Quantity:
4
Body Outside Diameter:
7.000 inches
Body Height:
21.468 inches
Filtration Rating In Microns:
10.0
Drop Pressure:
3.0 pounds per square inch
Differential Pressure:
100.0 pounds per square inch
Distance Between Mounting Hole Centers:
2.500 inches and 2.750 inches
Design Type:
Reusable
Tempurature Rating:
250.0 degrees fahrenheit
Filtering Element Quantity:
2
Maximum Operating Pressure:
150.0 pounds per square inch
Filtering Media Design:
Pleated single filtering media response
First Intake Connection Type:
Threaded internal pipe side near top
First Discharge Connection Relationship To Intake Connection:
Not identical
First Discharge Connection Type:
Threaded external pipe bottom
Distance From Bottom Of Body To Center Of Inlet:
22.875 inches
First Intake Thread Series Designator:
Unf
First Discharge Thread Series Designator:
Npt
First Intake Thread Size:

1.875 inches

## **NSN 4330-01-198-3043** Fluid Filter - Page 2 of 2



First Discharge Thread Size:
1.500 inches
First Intake Thread Class:
3b
First Intake Thread Direction:
Right-hand
First Discharge Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Special Features:
20.0 gpm
Material:
Aluminum sediment bowl and steel sediment bowl
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
Body and cover assembly (bolted flange)
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
424000