NSN 4330-01-198-4378

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-198-4378

View Online at https://aerobasegroup.com/nsn/4330-01-198-4378
Mounting Type:
Unthreaded hole side near top
Mounting Hole Diameter:
0.438 inches
Mounting Hole Quantity:
4
Body Outside Diameter:
7.000 inches
Body Height:
13.280 inches
Filtration Rating In Microns:
10.0
Drop Pressure:
3.00 pounds per square inch
Differential Pressure:
25.0 pounds per square inch
Distance Between Mounting Hole Centers:
5.250 inches
Design Type:
Nonreusable
Tempurature Rating:
250.0 degrees fahrenheit
Features Provided:
Differential pressure indicator
Filtering Element Quantity:
1
Maximum Operating Pressure:
400.0 pounds per square inch
Filtering Media Design:
Pleated single filtering media response
First Intake Connection Type:
Threaded internal pipe side near top
Second Intake Connection Relationship To First Intake Connection:
Identical
First Discharge Connection Relationship To Intake Connection:
Not identical
First Discharge Connection Type:
Threaded external pipe bottom
First Intake Thread Series Designator:
Nptf
First Discharge Thread Series Designator:

Nptf

NSN 4330-01-198-4378 Fluid Filter - Page 2 of 2



First Intake Thread Size:
1.500 inches
First Discharge Thread Size:
1.500 inches
First Intake Thread Direction:
Right-hand
First Discharge Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Special Features:
n-tank; outlet connection for options attachment
Material:
Steel container/cartridge
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
Body and cover assembly (bolted flange)
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A24000