
NSN 4330-01-199-1918

Fluid Filter - Page 1 of 2



Mounting Type:

Threaded hole top

Mounting Hole Quantity:

2

Body Outside Diameter:

4.500 inches

Body Height:

8.140 inches

Filtration Rating In Microns:

35.0 absolute

Distance Between Mounting Hole Centers:

2.250 inches

Design Type:

Reusable

Tempurature Rating:

Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Unc

Maximum Operating Pressure:

100.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Threaded internal tube head side

Mounting Facility Thread Size:

0.312 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Un

First Intake Thread Size:

0.750 inches

First Intake Thready Qty Per Inch (tpi):

12

First Intake Thread Class:

2b

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow



NSN 4330-01-199-1918

Fluid Filter - Page 2 of 2



Special Features:

Spin-on type element; corrosion resistant finish on head; differential pressure device port and bypass valve port plugged

Material:

Steel container/cartridge

Media For Which Designed:

Fuel/oil, hydrocarbon

Surface Treatment:

Paint container/cartridge

Style Designator:

Unthreaded shell

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A24000