## NSN 4330-01-199-1918



Fluid Filter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4330-01-199-1918 **Mounting Type:** Threaded hole top **Mounting Hole Quantity:** 2 **Body Outside Diameter:** 4.500 inches **Body Height:** 8.140 inches **Filtration Rating In Microns:** 35.0 absolute **Distance Between Mounting Hole Centers:** 2.250 inches **Design Type:** Reusable **Tempurature Rating:** Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit **Filtering Element Quantity:** 1 **Mounting Facility Thread Series Designator:** Unc **Maximum Operating Pressure:** 100.0 pounds per square inch Filtering Media Design: Pleated single filtering media response **First Intake Connection Type:** Threaded internal tube head side **Mounting Facility Thread Size:** 0.312 inches First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator:

First Intake Thread Size:
0.750 inches
First Intake Thready Qty Per Inch (tpi):
12
First Intake Thread Class:
2b
First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow

## NSN 4330-01-199-1918

Fluid Filter - Page 2 of 2



Special Features:			
Spin-on type element;	corrosion resistant finish on head;	differential pressure device port and bypas	ss valve port plugged

Steel container/cartridge

Media For Which Designed:

Fuel/oil, hydrocarbon

**Surface Treatment:** 

Paint container/cartridge

Style Designator:

Unthreaded shell

Shelf Life:

Material:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A24000