

View Online at <https://aerobasegroup.com/nsn/4330-01-200-5664>

Mounting Type:

Threaded hole top

Mounting Hole Quantity:

4

Filtration Rating In Microns:

10.0

Drop Pressure:

6.5 pounds per square inch

Distance Between Mounting Hole Centers:

2.380 inches and 6.750 inches

Design Type:

Reusable

Tempurature Rating:

Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit

Unit Quantity:

2

Features Provided:

By-pass valve and differential pressure indicator

Filtering Element Quantity:

2

Mounting Facility Thread Series Designator:

Unc

Maximum Operating Pressure:

200.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Plain face flange head side

Mounting Facility Thread Size:

0.375 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Flange Shape Style:

Rectangular w/threaded bolt holes

First Intake Flange Face Style:

Plain

First Intake Flange Thickness:

1.280 inches

First Intake Flange Length:

4.130 inches

First Intake Flange Width:

3.000 inches

Filtering System For Which Designed:

Full flow

Special Features:

90.0 gpm flow

Material:

Steel sediment bowl

Media For Which Designed:

Fuel/oil, hydrocarbon

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A24000