NSN 4330-01-200-5664



Fluid Filter Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4330-01-200-5664 **Mounting Type:** Threaded hole top **Mounting Hole Quantity: Filtration Rating In Microns:** 10.0 **Drop Pressure:** 6.5 pounds per square inch **Distance Between Mounting Hole Centers:** 2.380 inches and 6.750 inches **Design Type:** Reusable **Tempurature Rating:** Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit **Unit Quantity: Features Provided:** By-pass valve and differential pressure indicator **Filtering Element Quantity: Mounting Facility Thread Series Designator:** Unc **Maximum Operating Pressure:** 200.0 pounds per square inch Filtering Media Design: Pleated single filtering media response **First Intake Connection Type:** Plain face flange head side **Mounting Facility Thread Size:** 0.375 inches First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Flange Shape Style:

Rectangular w/threaded bolt holes

First Intake Flange Face Style:

Plain

First Intake Flange Thickness:

1.280 inches

First Intake Flange Length:

4.130 inches

First Intake Flange Width:

3.000 inches

NSN 4330-01-200-5664 Fluid Filter Assembly - Page 2 of 2



Filtering System For Which Designed:
Full flow
Special Features:
90.0 gpm flow
Material:
Steel sediment bowl
Media For Which Designed:
Fuel/oil, hydrocarbon
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A24000