

View Online at <https://aerobasegroup.com/nsn/4330-01-203-4257>

Mounting Type:

Threaded hole head

Mounting Hole Quantity:

4

Drop Pressure:

35.0 pounds per square inch

Distance Between Mounting Hole Centers:

4.000 inches

Design Type:

Reusable

Unit Quantity:

2

Features Provided:

Differential pressure indicator and drain plug

Filtering Element Quantity:

2

Mounting Facility Thread Series Designator:

Unf

Maximum Operating Pressure:

3000.0 pounds per square inch

First Intake Connection Type:

Recessed flange top

Mounting Facility Thread Size:

0.500 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

Second Discharge Connection Relationship To Preceding Connection:

Identical to first intake connection

First Intake Flange Shape Style:

Rectangular w/threaded bolt holes

First Intake Flange Face Style:

Recessed

First Intake Flange Thickness:

7.940 inches

First Intake Flange Length:

6.060 inches

First Intake Flange Width:

18.000 inches

First Intake Flange Recess Diameter:

2.125 inches

First Intake Flange Recess Depth:

0.305 inches

Filtering System For Which Designed:

Full flow

Special Features:

Inlet and outlet connections are located on the same surface of the filter body

Material:

Resin synthetic filtering medium

Media For Which Designed:

Fuel/oil, hydrocarbon

Specification Data:

81349-mil-f-24402d/sh/ government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A24000