

View Online at <https://aerobasegroup.com/nsn/4330-01-206-1951>

Mounting Type:

Threaded hole top side

Mounting Hole Quantity:

4

Body Outside Diameter:

4.570 inches

Body Height:

9.250 inches

Filtration Rating In Microns:

12.0 absolute

Differential Pressure:

25.0 pounds per square inch

Distance Between Mounting Hole Centers:

2.500 inches and 2.502 inches

Design Type:

Reusable

Tempurature Rating:

Between -45.0 degrees fahrenheit and 275.0 degrees fahrenheit

Features Provided:

Air bleed valve and by-pass valve and differential pressure indicator and thermal lockout

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Unc

Maximum Operating Pressure:

1000.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Threaded internal tube back

Mounting Facility Thread Size:

0.312 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Un

First Intake Thread Size:

1.0625 inches

First Intake Thready Qty Per Inch (tpi):

16

First Intake Thread Class:

3b

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

Low pressure, w/o anti-backflow device

Material:

Steel sediment bowl or stainless steel sediment bowl

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A24000