NSN 4330-01-211-8614

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-211-8614

Mounting Type:
Bracket w/drilled hole side
Mounting Hole Diameter:
0.465 inches
Mounting Hole Quantity:
2
Body Outside Diameter:
4.700 inches
Body Height:
21.740 inches
Filtration Rating In Microns:
6.0 absolute
Distance Between Mounting Hole Centers:
5.380 inches
Design Type:
Reusable
Tempurature Rating:
Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit
Features Provided:
By-pass valve and flow control valve
Bracket Quantity:
1
Filtering Element Quantity:
1
Maximum Operating Pressure:
6000.0 pounds per square inch
First Intake Connection Type:
Plain face flange head side
First Discharge Connection Relationship To Intake Connection:
Not identical
First Discharge Connection Type:
Plain face flange top
First Intake Flange Shape Style:
Oval w/threaded bolt holes
First Discharge Flange Shape Style:
Oval w/threaded bolt holes
First Intake Flange Face Style:
Plain
First Discharge Flange Face Style:
Plain
First Intake Flange Thickness:

0.620 inches

NSN 4330-01-211-8614 Fluid Filter - Page 2 of 2



First Discharge Flange Thickness:
0.620 inches
First Intake Flange Length:
Between 2.720 inches and 2.780 inches
First Discharge Flange Length:
Between 2.720 inches and 2.780 inches
First Intake Flange Width:
2.220 inches
First Discharge Flange Width:
2.220 inches
Filtering System For Which Designed:
Full flow or by-pass flow
Special Features:
Split flange per sae j518c
Material:
Steel sediment bowl
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
High pressure threaded body
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A24000