## NSN 4330-01-220-5812

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-220-5812

Mounting Type:
Threaded hole top
Mounting Hole Quantity:
4
Body Outside Diameter:
3.840 inches
Body Height:
7.640 inches
Filtration Rating In Microns:
25.0
Drop Pressure:
25.0 pounds per square inch
Differential Pressure:
7.5 pounds per square inch
Distance Between Mounting Hole Centers:
1.880 inches and 3.190 inches
Design Type:
Reusable
Tempurature Rating:
Between -40.0 degrees fahrenheit and 225.0 degrees fahrenheit
Features Provided:
By-pass valve
Filtering Element Quantity:
1
Mounting Facility Thread Series Designator:
Unc
Maximum Operating Pressure:
100.0 pounds per square inch
Filtering Media Design:
Pleated single filtering media response
First Intake Connection Type:
Threaded internal pipe head side
Mounting Facility Thread Size:
0.375 inches
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Thread Series Designator:
Nptf
First Intake Thread Size:
1.000 inches
First Intake Thread Direction:
Right-hand

## NSN 4330-01-220-5812

Fluid Filter - Page 2 of 2



Filtering System For Which Designed:
Full flow or partial flow
Special Features:
Spin-on type element
Material:
Steel body
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
Unthreaded shell
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A24000