## NSN 4330-01-231-2795

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-231-2795

Inlet connection and outlet connection top side  Filtration Rating In Microns: 20.0  Drop Pressure: 5.0 pounds per square inch  Design Type: Reusable  Tempurature Rating: 180.0 degrees fahrenheit  Filtering Element Quantity: 1  Maximum Operating Pressure: 300.0 pounds per square inch  Filtering Media Design: Sintered single filtering media response  First Intake Connection Type: Threaded internal pipe top side  Second Intake Connection Relationship To Intake Connection: Identical to second intake connection  Relationship To Preceding Connection:
Filtration Rating In Microns:  20.0  Drop Pressure:  5.0 pounds per square inch  Design Type:  Reusable  Tempurature Rating:  180.0 degrees fahrenheit  Filtering Element Quantity:  1  Maximum Operating Pressure:  300.0 pounds per square inch  Filtering Media Design:  Sintered single filtering media response  First Intake Connection Type:  Threaded internal pipe top side  Second Intake Connection Relationship To First Intake Connection:  Identical  First Discharge Connection Relationship To Intake Connection:  Identical to second intake connection
Drop Pressure:  5.0 pounds per square inch Design Type: Reusable Tempurature Rating: 180.0 degrees fahrenheit Filtering Element Quantity: 1 Maximum Operating Pressure: 300.0 pounds per square inch Filtering Media Design: Sintered single filtering media response First Intake Connection Type: Threaded internal pipe top side Second Intake Connection Relationship To First Intake Connection: Identical First Discharge Connection Relationship To Intake Connection: Identical to second intake connection
Drop Pressure: 5.0 pounds per square inch Design Type: Reusable Tempurature Rating: 180.0 degrees fahrenheit Filtering Element Quantity: 1 Maximum Operating Pressure: 300.0 pounds per square inch Filtering Media Design: Sintered single filtering media response First Intake Connection Type: Threaded internal pipe top side Second Intake Connection Relationship To First Intake Connection: Identical First Discharge Connection Relationship To Intake Connection: Identical to second intake connection
5.0 pounds per square inch  Design Type: Reusable  Tempurature Rating: 180.0 degrees fahrenheit  Filtering Element Quantity: 1  Maximum Operating Pressure: 300.0 pounds per square inch  Filtering Media Design: Sintered single filtering media response  First Intake Connection Type: Threaded internal pipe top side  Second Intake Connection Relationship To First Intake Connection: Identical  First Discharge Connection Relationship To Intake Connection: Identical to second intake connection
Design Type: Reusable Tempurature Rating: 180.0 degrees fahrenheit Filtering Element Quantity: 1 Maximum Operating Pressure: 300.0 pounds per square inch Filtering Media Design: Sintered single filtering media response First Intake Connection Type: Threaded internal pipe top side Second Intake Connection Relationship To First Intake Connection: Identical First Discharge Connection Relationship To Intake Connection: Identical to second intake connection
Tempurature Rating: 180.0 degrees fahrenheit Filtering Element Quantity: 1 Maximum Operating Pressure: 300.0 pounds per square inch Filtering Media Design: Sintered single filtering media response First Intake Connection Type: Threaded internal pipe top side Second Intake Connection Relationship To First Intake Connection: Identical First Discharge Connection Relationship To Intake Connection: Identical to second intake connection
Tempurature Rating:  180.0 degrees fahrenheit  Filtering Element Quantity:  1  Maximum Operating Pressure:  300.0 pounds per square inch  Filtering Media Design:  Sintered single filtering media response  First Intake Connection Type:  Threaded internal pipe top side  Second Intake Connection Relationship To First Intake Connection:  Identical  First Discharge Connection Relationship To Intake Connection:  Identical to second intake connection
180.0 degrees fahrenheit  Filtering Element Quantity:  1  Maximum Operating Pressure: 300.0 pounds per square inch  Filtering Media Design: Sintered single filtering media response  First Intake Connection Type: Threaded internal pipe top side  Second Intake Connection Relationship To First Intake Connection: Identical  First Discharge Connection Relationship To Intake Connection: Identical to second intake connection
Filtering Element Quantity:  1  Maximum Operating Pressure: 300.0 pounds per square inch  Filtering Media Design: Sintered single filtering media response  First Intake Connection Type: Threaded internal pipe top side  Second Intake Connection Relationship To First Intake Connection: Identical  First Discharge Connection Relationship To Intake Connection: Identical to second intake connection
Maximum Operating Pressure: 300.0 pounds per square inch Filtering Media Design: Sintered single filtering media response First Intake Connection Type: Threaded internal pipe top side Second Intake Connection Relationship To First Intake Connection: Identical First Discharge Connection Relationship To Intake Connection: Identical to second intake connection
Maximum Operating Pressure:  300.0 pounds per square inch  Filtering Media Design:  Sintered single filtering media response  First Intake Connection Type:  Threaded internal pipe top side  Second Intake Connection Relationship To First Intake Connection:  Identical  First Discharge Connection Relationship To Intake Connection:  Identical to second intake connection
300.0 pounds per square inch  Filtering Media Design: Sintered single filtering media response  First Intake Connection Type: Threaded internal pipe top side  Second Intake Connection Relationship To First Intake Connection: Identical  First Discharge Connection Relationship To Intake Connection: Identical to second intake connection
Filtering Media Design: Sintered single filtering media response First Intake Connection Type: Threaded internal pipe top side Second Intake Connection Relationship To First Intake Connection: Identical First Discharge Connection Relationship To Intake Connection: Identical to second intake connection
Sintered single filtering media response  First Intake Connection Type:  Threaded internal pipe top side  Second Intake Connection Relationship To First Intake Connection:  Identical  First Discharge Connection Relationship To Intake Connection:  Identical to second intake connection
First Intake Connection Type:  Threaded internal pipe top side  Second Intake Connection Relationship To First Intake Connection:  Identical  First Discharge Connection Relationship To Intake Connection:  Identical to second intake connection
Threaded internal pipe top side  Second Intake Connection Relationship To First Intake Connection: Identical  First Discharge Connection Relationship To Intake Connection: Identical to second intake connection
Second Intake Connection Relationship To First Intake Connection:  Identical  First Discharge Connection Relationship To Intake Connection:  Identical to second intake connection
Identical  First Discharge Connection Relationship To Intake Connection:  Identical to second intake connection
First Discharge Connection Relationship To Intake Connection:  Identical to second intake connection
Identical to second intake connection
Second Discharge Connection Relationship To Preceding Connection:
Identical to first discharge connection
First Intake Thread Series Designator:
Npt
First Intake Thread Size:
0.375 inches
First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Material:
Zinc body
Media For Which Designed:
Air
Style Designator:
High pressure threaded body
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4330-01-231-2795

Fluid Filter - Page 2 of 2



Demilitarization:

No

Fiig:

A24000