# NSN 4330-01-236-2791

Fluid Filter Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-236-2791

# Mounting Type:

Bracket center

## **Drop Pressure:**

10.0 pounds per square inch

## **Differential Pressure:**

600.0 pounds per square inch

#### Design Type:

Nonreusable

#### **Tempurature Rating:**

Between -40.0 degrees fahrenheit and 250.0 degrees fahrenheit

#### **Unit Quantity:**

1

#### Bracket Quantity:

2

#### Filtering Element Quantity:

2

# Maximum Operating Pressure:

150.0 pounds per square inch

# Filtering Media Design:

Pleated 1st filtering media response

#### First Intake Connection Type:

Threaded internal pipe side near top

## First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

## First Intake Thread Series Designator:

Npt

#### First Intake Thread Size:

1.250 inches

First Intake Thread Direction:

**Right-hand** 

#### Filtering System For Which Designed:

By-pass flow

Material:

Steel container/cartridge

# Media For Which Designed:

Fuel/oil, hydrocarbon

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

# NSN 4330-01-236-2791

Fluid Filter Assembly - Page 2 of 2

**Fiig:** A24000

