NSN 4330-01-236-4528

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-236-4528

| Thread Direction: |
|---|
| Right-hand |
| Mounting Type: |
| Inlet connection end and outlet connection end |
| Body Length: |
| 5.750 inches |
| Body Outside Diameter: |
| 1.500 inches |
| Filtration Rating In Microns: |
| 3.0 absolute |
| End Application: |
| Ground support equipment for f/a-18 hornet aircraft |
| Design Type: |
| Reusable |
| Filtering Element Quantity: |
| 1 |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch |
| Filtering Media Design: |
| Pleated single filtering media response |
| First Intake Connection Type: |
| Threaded external tube end |
| Second Intake Connection Relationship To First Intake Connection: |
| Identical |
| First Discharge Connection Relationship To Intake Connection: |
| Identical to first intake connection |
| First Intake Thread Series Designator: |
| Unf |
| First Intake Thread Size: |
| 0.5625 inches |
| First Intake Thread Class: |
| 2a |
| First Intake Thread Direction: |
| Right-hand |
| Filtering System For Which Designed: |
| Full flow |
| Special Features: |
| length 7.438; removeable outlet fitting |
| Material: |
| Rubber synthetic seal |
| Material Specification: |
| Why t 700/6 to military englished and a material response hady |

Ww-t-700/6, t6 military specification single material response body

NSN 4330-01-236-4528

Fluid Filter - Page 2 of 2

Mil-p-25732 spec.



| Media For Which Designed: |
|---|
| Fuel/oil, hydrocarbon |
| Surface Treatment: |
| Anodize body |
| Surface Treatment Specification: |
| Mil-a-8625, ty3, cl1 assn standard single treatment response body |
| Style Designator: |
| Inline (hydraulic) |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A24000 |
| Mil-std (military Standard): |