## NSN 4330-01-241-8935

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-241-8935

#### Mounting Type:

Threaded stud head side

#### Mounting Hole Quantity:

2

## Body Length:

4.500 inches

#### Body Width:

4.500 inches

#### **Body Height:**

9.000 inches

#### **Filtration Rating In Microns:**

1.0

#### Drop Pressure:

0.05 pounds per square inch

#### **Distance Between Mounting Hole Centers:**

1.500 inches

#### Perforation Diameter:

0.079 inches

#### Perforation Quantity:

67.0 per square inch

#### Design Type:

Reusable

#### Tempurature Rating:

300.0 degrees fahrenheit

#### **Features Provided:**

Magnet

#### Filtering Element Quantity:

1

#### Mounting Facility Thread Series Designator:

Unc

## Maximum Operating Pressure:

300.0 pounds per square inch

## Filtering Media Design:

Perforated single filtering media response

## First Intake Connection Type:

Threaded internal tube head side

## Mounting Facility Thread Size:

0.375 inches

## First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

## Distance From Bottom Of Body To Center Of Inlet:

7.625 inches

# NSN 4330-01-241-8935

Fluid Filter - Page 2 of 2



First Intake Thread Series Designator: Un First Intake Thread Size: 1.312 inches First Intake Thready Qty Per Inch (tpi): 12 First Intake Thread Class: 3b First Intake Thread Direction: **Right-hand** Filtering System For Which Designed: Full flow **Special Features:** Includes 3 magnet separator element; 12.5 gpm; in-line application Material: Steel sediment bowl Media For Which Designed: Fuel/oil, hydrocarbon Style Designator: Tee type (hydraulic) Supplementary Features: Hex wenching device element Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A24000