NSN 4330-01-241-8935

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-241-8935

| Mounting Type: |
|---|
| Threaded stud head side |
| Mounting Hole Quantity: |
| 2 |
| Body Length: |
| 4.500 inches |
| Body Width: |
| 4.500 inches |
| Body Height: |
| 9.000 inches |
| Filtration Rating In Microns: |
| 1.0 |
| Drop Pressure: |
| 0.05 pounds per square inch |
| Distance Between Mounting Hole Centers: |
| 1.500 inches |
| Perforation Diameter: |
| 0.079 inches |
| Perforation Quantity: |
| 67.0 per square inch |
| Design Type: |
| Reusable |
| Tempurature Rating: |
| 300.0 degrees fahrenheit |
| Features Provided: |
| Magnet |
| Filtering Element Quantity: |
| 1 |
| Mounting Facility Thread Series Designator: |
| Unc |
| Maximum Operating Pressure: |
| 300.0 pounds per square inch |
| Filtering Media Design: |
| Perforated single filtering media response |
| First Intake Connection Type: |
| Threaded internal tube head side |
| Mounting Facility Thread Size: |
| 0.375 inches |
| First Discharge Connection Relationship To Intake Connection: |
| Identical to first intake connection |
| Distance From Bottom Of Body To Center Of Inlet: |

7.625 inches

NSN 4330-01-241-8935 Fluid Filter - Page 2 of 2



| First Intake Thread Series Designator: | |
|--|--|
| Un | |
| First Intake Thread Size: | |
| 1.312 inches | |
| First Intake Thready Qty Per Inch (tpi): | |
| 12 | |
| First Intake Thread Class: | |
| 3b | |
| First Intake Thread Direction: | |
| Right-hand | |
| Filtering System For Which Designed: | |
| Full flow | |
| Special Features: | |
| Includes 3 magnet separator element; 12.5 gpm; in-line application | |
| Material: | |
| Steel sediment bowl | |
| Media For Which Designed: | |
| Fuel/oil, hydrocarbon | |
| Style Designator: | |
| Tee type (hydraulic) | |
| Supplementary Features: | |
| Hex wenching device element | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A24000 | |
| | |