NSN 4330-01-249-3509

Fluid Filter - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4330-01-249-3509

Mounting Type:

Threaded hole top

Mounting Hole Quantity:

4

Body Outside Diameter:

3.440 inches

Body Height:

9.170 inches

Filtration Rating In Microns:

25.0 absolute and 10.0

Drop Pressure:

23.5 pounds per square inch

Distance Between Mounting Hole Centers:

2.250 inches and 3.720 inches

Design Type:

Reusable

Tempurature Rating:

Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit

Features Provided:

By-pass valve and differential pressure indicator and drain plug

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Unc

Maximum Operating Pressure:

6000.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Threaded internal tube head

Mounting Facility Thread Size:

0.438 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Un

First Intake Thread Size:

1.0625 inches

First Intake Thready Qty Per Inch (tpi):

12

First Intake Thread Class:

2b



NSN 4330-01-249-3509

Fluid Filter - Page 2 of 2



First Intake Thread Direction: Right-hand Filtering System For Which Designed: Full flow or by-pass flow **Special Features:** Visual differential pressure indicator; 50psi bypass valve Material: Steel sediment bowl Media For Which Designed: Fuel/oil, hydrocarbon Surface Treatment: Phosphate sediment bowl Style Designator: High pressure threaded body Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A24000