

View Online at <https://aerobasegroup.com/nsn/4330-01-250-2799>

**Mounting Type:**

Unthreaded hole head side

**Mounting Hole Diameter:**

0.266 inches

**Mounting Hole Quantity:**

2

**Body Outside Diameter:**

4.000 inches

**Body Height:**

8.570 inches

**Filtration Rating In Microns:**

20.0

**Differential Pressure:**

50.0 pounds per square inch

**Distance Between Mounting Hole Centers:**

3.125 inches

**Design Type:**

Reusable

**Temperature Rating:**

Between -40.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Features Provided:**

By-pass valve and drain plug

**Filtering Element Quantity:**

1

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Filtering Media Design:**

Pleated single filtering media response

**First Intake Connection Type:**

Threaded internal tube head side

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**First Intake Thread Series Designator:**

Un

**First Intake Thread Size:**

1.062 inches

**First Intake Thread Qty Per Inch (tpi):**

12

**First Intake Thread Class:**

3b

**First Intake Thread Direction:**

Right-hand

**Filtering System For Which Designed:**

Full flow

**Special Features:**

Pop-up visual indicator

**Material:**

Rubber buna n seal

**Media For Which Designed:**

Fuel/oil, hydrocarbon

**Surface Treatment:**

Anodize body

**Style Designator:**

High pressure threaded body

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A24000