# NSN 4330-01-250-2799

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-250-2799

## Mounting Type:

Unthreaded hole head side

### Mounting Hole Diameter:

0.266 inches

# Mounting Hole Quantity:

2

### **Body Outside Diameter:**

4.000 inches

#### **Body Height:**

8.570 inches

#### **Filtration Rating In Microns:**

20.0

## Differential Pressure:

50.0 pounds per square inch

#### **Distance Between Mounting Hole Centers:**

3.125 inches

#### **Design Type:**

Reusable

## **Tempurature Rating:**

Between -40.0 degrees fahrenheit and 250.0 degrees fahrenheit

## **Features Provided:**

By-pass valve and drain plug

# Filtering Element Quantity:

1

# Maximum Operating Pressure:

3000.0 pounds per square inch

# Filtering Media Design:

Pleated single filtering media response

# First Intake Connection Type:

Threaded internal tube head side

# First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

# First Intake Thread Series Designator:

Un

# First Intake Thread Size:

1.062 inches

First Intake Thready Qty Per Inch (tpi):

12

First Intake Thread Class:

3b

First Intake Thread Direction:

Right-hand

# NSN 4330-01-250-2799

Fluid Filter - Page 2 of 2



Filtering System For Which Designed:

Full flow

#### **Special Features:**

Pop-up visual indicator

Material:

Rubber buna n seal

# Media For Which Designed:

Fuel/oil, hydrocarbon

## Surface Treatment:

Anodize body

#### Style Designator:

High pressure threaded body

Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

## Fiig:

A24000