## NSN 4330-01-253-2851

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-253-2851

Mounting Type:
Threaded hole top
Mounting Hole Quantity:
2
Body Outside Diameter:
5.375 inches
Body Height:
9.562 inches
Filtration Rating In Microns:
10.0
Drop Pressure:
25.0 pounds per square inch
Differential Pressure:
10.5 pounds per square inch
Distance Between Mounting Hole Centers:
3.188 inches
Design Type:
Reusable
Tempurature Rating:
Between -40.0 degrees fahrenheit and 225.0 degrees fahrenheit
Features Provided:
By-pass valve
Filtering Element Quantity:
1
Mounting Facility Thread Series Designator:
Unc
Maximum Operating Pressure:
100.0 pounds per square inch
Filtering Media Design:
Pleated single filtering media response
First Intake Connection Type:
Threaded internal pipe head side
Mounting Facility Thread Size:
0.375 inches
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Thread Series Designator:
Nptf
First Intake Thread Size:
1.500 inches
First Intake Thread Direction:

Right-hand

## NSN 4330-01-253-2851

Fluid Filter - Page 2 of 2

No Fiig: A24000



Filtering System For Which Designed:
Full flow or partial flow
Special Features:
Spin-on type element; $$ w/ pressure gauge at location "d"; $$ 1/8 in. Nptf gauge port
Material:
Steel body
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
Unthreaded shell
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: