

View Online at <https://aerobasegroup.com/nsn/4330-01-253-2851>

**Mounting Type:**

Threaded hole top

**Mounting Hole Quantity:**

2

**Body Outside Diameter:**

5.375 inches

**Body Height:**

9.562 inches

**Filtration Rating In Microns:**

10.0

**Drop Pressure:**

25.0 pounds per square inch

**Differential Pressure:**

10.5 pounds per square inch

**Distance Between Mounting Hole Centers:**

3.188 inches

**Design Type:**

Reusable

**Temperature Rating:**

Between -40.0 degrees fahrenheit and 225.0 degrees fahrenheit

**Features Provided:**

By-pass valve

**Filtering Element Quantity:**

1

**Mounting Facility Thread Series Designator:**

Unc

**Maximum Operating Pressure:**

100.0 pounds per square inch

**Filtering Media Design:**

Pleated single filtering media response

**First Intake Connection Type:**

Threaded internal pipe head side

**Mounting Facility Thread Size:**

0.375 inches

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**First Intake Thread Series Designator:**

Nptf

**First Intake Thread Size:**

1.500 inches

**First Intake Thread Direction:**

Right-hand

**Filtering System For Which Designed:**

Full flow or partial flow

**Special Features:**

Spin-on type element; w/ pressure gauge at location "d"; 1/8 in. Nptf gauge port

**Material:**

Steel body

**Media For Which Designed:**

Fuel/oil, hydrocarbon

**Style Designator:**

Unthreaded shell

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A24000