

View Online at <https://aerobasegroup.com/nsn/4330-01-257-3638>

Mounting Type:

Bracket w/drilled hole bottom

Mounting Hole Diameter:

0.625 inches

Mounting Hole Quantity:

4

Body Outside Diameter:

17.625 inches

Body Height:

33.250 inches

Filtration Rating In Microns:

5.0

Differential Pressure:

20.0 pounds per square inch

Design Type:

Nonreusable

Tempurature Rating:

250.0 degrees fahrenheit

Features Provided:

Air bleed valve and differential pressure indicator and flow control valve

Bracket Quantity:

2

Filtering Element Quantity:

5

Maximum Operating Pressure:

150.0 pounds per square inch

Filtering Media Design:

Spun single filtering media response

First Intake Connection Type:

Threaded internal pipe side

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

Distance From Bottom Of Body To Center Of Inlet:

2.938 inches

First Intake Thread Series Designator:

Npt

First Intake Thread Size:

2.000 inches

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

Outlet 28.000 in. From bottom of body to center of outlet, 180.0 degrees apart from inlet; interior lined w/epoxy coating; includes only manual controls, diesel version of elements; flow rate 65 gpm; sight glass assembly and manual drain valve

Material:

Steel body

Media For Which Designed:

Fuel/oil, hydrocarbon

Surface Treatment:

Paint body

Style Designator:

Floor mounted split body (bolted flange)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000