# NSN 4330-01-257-8846

Fluid Filter Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-257-8846

# Mounting Type:

Threaded hole side

# Mounting Hole Quantity:

12

# Filtration Rating In Microns:

25.0

### **Distance Between Mounting Hole Centers:**

1.250 inches and 13.000 inches

#### Wire Diameter:

0.0018 inches

### Mesh Size:

400.0

#### Design Type:

Reusable

#### Tempurature Rating:

Between -40.0 degrees fahrenheit and 225.0 degrees fahrenheit

# Unit Quantity:

2

#### **Features Provided:**

By-pass valve and drain plug and magnet and switch-over valve

#### **Filtering Element Quantity:**

2

# Mounting Facility Thread Series Designator:

Unc

#### Maximum Operating Pressure:

750.0 pounds per square inch

#### Filtering Media Design:

Mesh single filtering media response

### First Intake Connection Type:

Raised face flange side

#### Mounting Facility Thread Size:

0.500 inches

#### First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

#### First Intake Flange Outside Diameter:

10.000 inches

### First Intake Flange Shape Style:

Round w/unthreaded bolt holes

### First Intake Flange Face Style:

Raised

### First Intake Flange Thickness:

1.250 inches

# NSN 4330-01-257-8846

Fluid Filter Assembly - Page 2 of 2



First Intake Flange Raised Face Height:

0.062 inches

# First Intake Flange Raised Face Diameter:

6.188 inches

# Filtering System For Which Designed:

Full flow or by-pass flow

# **Special Features:**

Electric dirt alarm

### Material:

Stainless steel filtering medium

#### Media For Which Designed:

Fuel/oil, hydrocarbon

Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

No

# Fiig:

A24000