## NSN 4330-01-258-5202

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-258-5202

Mounting Type:
Unthreaded hole side near top
Mounting Hole Diameter:
0.438 inches
Mounting Hole Quantity:
4
Body Outside Diameter:
7.000 inches
Body Height:
16.667 inches
Filtration Rating In Microns:
10.0 absolute
Drop Pressure:
3.0 pounds per square inch
Differential Pressure:
25.0 pounds per square inch
Distance Between Mounting Hole Centers:
5.250 inches
Design Type:
Reusable
Tempurature Rating:
250.0 degrees fahrenheit
Features Provided:
Differential pressure indicator and antidrain back device
Filtering Element Quantity:
1
Maximum Operating Pressure:
400.0 pounds per square inch
Filtering Media Design:
Pleated single filtering media response
First Intake Connection Type:
Threaded internal tube top side
Second Intake Connection Relationship To First Intake Connection:
Identical
First Discharge Connection Relationship To Intake Connection:
Not identical
First Discharge Connection Type:
Threaded external pipe bottom
First Intake Thread Series Designator:
Unf
First Discharge Thread Series Designator:

Nptf

## **NSN 4330-01-258-5202** Fluid Filter - Page 2 of 2



First Intake Thread Size:
1.875 inches
First Discharge Thread Size:
1.500 inches
First Intake Thread Class:
3b
First Intake Thread Direction:
Right-hand
First Discharge Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Special Features:
In-tank type
Material:
Steel body
Media For Which Designed:
Fuel/oil, hydrocarbon
Surface Treatment:
Anodize container/cartridge
Style Designator:
Body and cover assembly (bolted flange)
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A24000