NSN 4330-01-259-0363

Fluid Filter Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-259-0363

Mounting Type:
Threaded hole side
Mounting Hole Quantity:
12
Filtration Rating In Microns:
25.0
Distance Between Mounting Hole Centers:
1.250 inches and 11.750 inches
Wire Diameter:
0.0018 inches
Mesh Size:
400.0
Design Type:
Reusable
Tempurature Rating:
Between -40.0 degrees fahrenheit and 225.0 degrees fahrenheit
Unit Quantity:
2
Features Provided:
By-pass valve and drain plug and magnet and switch-over valve
Filtering Element Quantity:
2
Mounting Facility Thread Series Designator:
Unc
Maximum Operating Pressure:
750.0 pounds per square inch
Filtering Media Design:
Mesh single filtering media response
First Intake Connection Type:
Raised face flange center
Mounting Facility Thread Size:
0.500 inches
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Flange Outside Diameter:
6.500 inches
First Intake Flange Shape Style:
Round w/unthreaded bolt holes
First Intake Flange Face Style:
Raised
First Intake Flange Thickness:

1.312 inches

NSN 4330-01-259-0363

Fluid Filter Assembly - Page 2 of 2



First Intake Flange Raised Face Height:
0.375 inches
First Intake Flange Raised Face Diameter
3.312 inches
Filtering System For Which Designed:
Full flow or by-pass flow
Special Features:
25 psi bypass; electrical dirt alarm
Material:
Stainless steel filtering medium
Media For Which Designed:
Fuel/oil, hydrocarbon
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A24000