

View Online at <https://aerobasegroup.com/nsn/4330-01-259-0363>

**Mounting Type:**

Threaded hole side

**Mounting Hole Quantity:**

12

**Filtration Rating In Microns:**

25.0

**Distance Between Mounting Hole Centers:**

1.250 inches and 11.750 inches

**Wire Diameter:**

0.0018 inches

**Mesh Size:**

400.0

**Design Type:**

Reusable

**Temperature Rating:**

Between -40.0 degrees fahrenheit and 225.0 degrees fahrenheit

**Unit Quantity:**

2

**Features Provided:**

By-pass valve and drain plug and magnet and switch-over valve

**Filtering Element Quantity:**

2

**Mounting Facility Thread Series Designator:**

Unc

**Maximum Operating Pressure:**

750.0 pounds per square inch

**Filtering Media Design:**

Mesh single filtering media response

**First Intake Connection Type:**

Raised face flange center

**Mounting Facility Thread Size:**

0.500 inches

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**First Intake Flange Outside Diameter:**

6.500 inches

**First Intake Flange Shape Style:**

Round w/unthreaded bolt holes

**First Intake Flange Face Style:**

Raised

**First Intake Flange Thickness:**

1.312 inches

**First Intake Flange Raised Face Height:**

0.375 inches

**First Intake Flange Raised Face Diameter:**

3.312 inches

**Filtering System For Which Designed:**

Full flow or by-pass flow

**Special Features:**

25 psi bypass; electrical dirt alarm

**Material:**

Stainless steel filtering medium

**Media For Which Designed:**

Fuel/oil, hydrocarbon

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A24000