NSN 4330-01-261-1108

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-261-1108

| · | | | | | | |
|---|--|--|--|--|--|--|
| Mounting Type: | | | | | | |
| Inlet connection line and outlet connection line | | | | | | |
| Body Outside Diameter: | | | | | | |
| 1.630 inches | | | | | | |
| Body Height: | | | | | | |
| 3.630 inches | | | | | | |
| Filtration Rating In Microns: | | | | | | |
| 5.0 | | | | | | |
| Design Type: | | | | | | |
| Reusable | | | | | | |
| Tempurature Rating: | | | | | | |
| 175.0 degrees fahrenheit | | | | | | |
| Features Provided: | | | | | | |
| Drain cock | | | | | | |
| Filtering Element Quantity: | | | | | | |
| 1 | | | | | | |
| Maximum Operating Pressure: | | | | | | |
| 250.0 pounds per square inch | | | | | | |
| Filtering Media Design: | | | | | | |
| Cellular single filtering media response | | | | | | |
| First Intake Connection Type: | | | | | | |
| Threaded internal pipe head side | | | | | | |
| First Discharge Connection Relationship To Intake Connection: | | | | | | |
| Identical to first intake connection | | | | | | |
| First Intake Thread Series Designator: | | | | | | |
| Npt | | | | | | |
| First Intake Thread Size: | | | | | | |
| 0.250 inches | | | | | | |
| First Intake Thread Direction: | | | | | | |
| Right-hand | | | | | | |
| Filtering System For Which Designed: | | | | | | |
| Full flow | | | | | | |
| Special Features: | | | | | | |
| Manual drain | | | | | | |
| Material: | | | | | | |
| Zinc sediment bowl | | | | | | |
| Media For Which Designed: | | | | | | |
| Air | | | | | | |
| Style Designator: | | | | | | |
| High pressure threaded body | | | | | | |
| Shelf Life: | | | | | | |

N/a

NSN 4330-01-261-1108

Fluid Filter - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A24000