# NSN 4330-01-273-3375

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-273-3375

### Mounting Type:

Unthreaded hole top

# Mounting Hole Diameter:

0.350 inches

# Mounting Hole Quantity:

4

# Body Length:

7.310 inches

#### **Body Outside Diameter:**

2.900 inches

**Body Height:** 

12.640 inches

#### **Filtration Rating In Microns:**

3.0 absolute

Drop Pressure:

38.5 pounds per square inch

#### **Distance Between Mounting Hole Centers:**

1.250 inches and 3.500 inches

Design Type:

Reusable

## Tempurature Rating:

Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit

#### **Features Provided:**

Differential pressure indicator

## Filtering Element Quantity:

1

#### Maximum Operating Pressure:

3000.0 pounds per square inch

#### Filtering Media Design:

Pleated single filtering media response

#### First Intake Connection Type:

Plain face flange top

#### First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

#### First Intake Flange Shape Style:

Rectangular w/unthreaded bolt holes

#### First Intake Flange Length:

1.810 inches

## First Intake Flange Width:

4.000 inches

#### Filtering System For Which Designed:

Full flow

# NSN 4330-01-273-3375

Fluid Filter - Page 2 of 2



#### **Special Features:**

Electric switch indicator per ms3102r10sl-3p; manifold top mtg; ports counterbore for 117 size o-rings

#### Material:

Rubber buna n seal

# Media For Which Designed:

Fuel/oil, hydrocarbon

## Surface Treatment:

Anodize sediment bowl

## Style Designator:

High pressure threaded body

## Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A24000