

View Online at <https://aerobasegroup.com/nsn/4330-01-280-8407>

Mounting Type:

Threaded hole top

Mounting Hole Quantity:

6

Body Length:

5.250 inches

Body Width:

2.420 inches

Body Height:

12.270 inches

Filtration Rating In Microns:

33.0

Drop Pressure:

6.0 pounds per square inch

Distance Between Mounting Hole Centers:

0.750 inches and 1.880 inches

Design Type:

Reusable

Temperature Rating:

Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit

Features Provided:

By-pass valve and differential pressure indicator

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Unc

Maximum Operating Pressure:

200.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Threaded internal tube head side

Mounting Facility Thread Size:

0.312 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

Distance From Bottom Of Body To Center Of Inlet:

10.750 inches

First Intake Thread Series Designator:

Un

First Intake Thread Size:

1.625 inches

First Intake Thready Qty Per Inch (tpi):

12

First Intake Thread Class:

2b

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

15 psi bypass

Material:

Steel sediment bowl

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

Tee type (hydraulic)

Departure From Cited Document:

Mounting bracket must be drilled with new holes to mount the "new filter"

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000