

View Online at <https://aerobasegroup.com/nsn/4330-01-282-8587>

Mounting Type:

Unthreaded hole bottom

Mounting Hole Quantity:

4

Body Length:

Between 11.250 inches and 11.500 inches

Body Width:

Between 8.625 inches and 8.875 inches

Body Height:

Between 16.375 inches and 17.250 inches

Differential Pressure:

5.0 pounds per square inch

Distance Between Mounting Hole Centers:

Between 6.500 inches and 8.500 inches

Design Type:

Reusable

Tempurature Rating:

Between 40.0 degrees fahrenheit and 160.0 degrees fahrenheit

Features Provided:

By-pass valve and drain cock

Filtering Element Quantity:

1

Maximum Operating Pressure:

300.0 pounds per square inch

Filtering Media Design:

Perforated single filtering media response

First Intake Connection Type:

Raised face flange top

First Discharge Connection Relationship To Intake Connection:

Not identical

First Discharge Connection Type:

Plain face flange end

First Intake Flange Shape Style:

Hexagon w/threaded bolt holes

First Discharge Flange Shape Style:

Rectangular w/threaded bolt holes

First Intake Flange Face Style:

Plain

First Discharge Flange Face Style:

Plain

Err Default:

Err default

Err Default:

Err default

Err Default:

Err default

Filtering System For Which Designed:

Full flow

Special Features:

Micron rating 238; inlet and ourlet 3.000 in. Dia, 4 ea thd holes 5/8-11unc-2bon 2.438 in by 4.188 in

Material:

Stainless steel filtering medium

Media For Which Designed:

Fuel/oil, hydrocarbon

Surface Treatment:

Paint body

Surface Treatment Specification:

Mil-r-2323g, type1 military specification single treatment response body

Style Designator:

High pressure angle strainer w/bolted cover

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000

Mil-std (military Standard):

Mil-r-2323g spec.