# NSN 4330-01-291-1819

Fluid Filter - Page 1 of 2



#### Mounting Type:

Threaded hole top

## Mounting Hole Quantity:

6

## Body Outside Diameter:

3.750 inches

## Body Width:

1.870 inches

#### **Body Height:**

7.380 inches

#### Filtration Rating In Microns:

25.0

## Design Type:

Reusable

#### Tempurature Rating:

Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit

#### Filtering Element Quantity:

1

#### Mounting Facility Thread Series Designator:

Unc

## Maximum Operating Pressure:

200.0 pounds per square inch

## Filtering Media Design:

Pleated single filtering media response

#### First Intake Connection Type:

Threaded internal tube head side

#### Mounting Facility Thread Size:

0.312 inches

## First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

## Distance From Bottom Of Body To Center Of Inlet:

6.630 inches

#### First Intake Thread Series Designator:

Un

#### First Intake Thread Size:

1.062 inches

## First Intake Thready Qty Per Inch (tpi):

12

# First Intake Thread Class:

3b

# First Intake Thread Direction:

Right-hand



# NSN 4330-01-291-1819

Fluid Filter - Page 2 of 2



# Filtering System For Which Designed:

Full flow

# **Special Features:**

Mtg holes 5/16unc-28 x 0.50in.Dp; no bypass, no indicator, no gauge

Material:

Rubber buna n seal

# Media For Which Designed:

Fuel/oil, hydrocarbon

# Style Designator:

Unthreaded shell

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A24000