

View Online at <https://aerobasegroup.com/nsn/4330-01-303-5943>

Mounting Type:

Threaded hole bottom

Mounting Hole Quantity:

4

Body Length:

8.610 inches

Body Width:

8.640 inches

Body Height:

15.690 inches

Filtration Rating In Microns:

3.0 absolute

Differential Pressure:

50.0 pounds per square inch

Distance Between Mounting Hole Centers:

4.000 inches and 4.000 inches

Design Type:

Reusable

Temperature Rating:

Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit

Features Provided:

Air bleed valve and by-pass valve and differential pressure indicator and drain plug

Bracket Quantity:

1

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Un

Maximum Operating Pressure:

400.0 pounds per square inch

Filtering Media Design:

Pleated all filtering media responses

First Intake Connection Type:

Raised face flange side

Mounting Facility Thread Size:

0.500 inches

First Discharge Connection Relationship To Intake Connection:

Not identical

First Discharge Connection Type:

Plain face flange bottom

Distance From Bottom Of Body To Center Of Inlet:

2.320 inches

First Intake Flange Shape Style:

Rectangular w/threaded bolt holes

First Discharge Flange Shape Style:

Rectangular w/threaded bolt holes

First Intake Flange Face Style:

Plain

First Discharge Flange Face Style:

Plain

First Intake Flange Thickness:

0.620 inches

First Discharge Flange Thickness:

0.620 inches

First Intake Flange Length:

2.906 inches

Err Default:

Err default

First Intake Flange Width:

3.750 inches

Err Default:

Err default

Filtering System For Which Designed:

By-pass flow or full flow

Special Features:

2ea drain ports 90.0deg on either side of inlet; cover has central fastening facility w/handle; split flange ports per sae j518c

Material:

Rubber buna n seal

Media For Which Designed:

Fuel/oil, hydrocarbon and water and water/alcohol mixture

Surface Treatment:

Anodize body

Style Designator:

High pressure angle strainer w/bolted cover

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A24000