NSN 4330-01-306-6429

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-306-6429

Mounting Type:

Unthreaded hole side near top

Mounting Hole Diameter:

0.438 inches

Mounting Hole Quantity:

4

Body Outside Diameter:

6.375 inches

Body Height:

16.667 inches

Filtration Rating In Microns:

10.0

Drop Pressure:

5.0 pounds per square inch

Differential Pressure:

25.0 pounds per square inch

Distance Between Mounting Hole Centers:

5.250 inches

Design Type:

Reusable

Tempurature Rating:

250.0 degrees fahrenheit

Features Provided:

Differential pressure indicator and antidrain back device

Filtering Element Quantity:

1

Maximum Operating Pressure:

400.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Threaded internal pipe side near top

Second Intake Connection Relationship To First Intake Connection:

Identical

First Discharge Connection Relationship To Intake Connection:

Not identical

First Discharge Connection Type:

Threaded external pipe bottom

First Intake Thread Series Designator:

Nptf

First Discharge Thread Series Designator:

Nptf

NSN 4330-01-306-6429 Fluid Filter - Page 2 of 2



First Intake Thread Size:
1.500 inches
First Discharge Thread Size:
1.500 inches
First Intake Thread Direction:
Right-hand
Second Discharge Thread Direction:
Right-hand
First Discharge Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Special Features:
In-tank; outlet connection for check valve; 5.000in. Diameter hole req for installation
Material:
Steel body
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
Body and cover assembly (bolted flange)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A24000