NSN 4330-01-313-2178

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-313-2178

| Mounting Type: |
|---|
| Threaded hole top |
| Mounting Hole Quantity: |
| 2 |
| Body Outside Diameter: |
| 5.380 inches |
| Body Height: |
| 9.560 inches |
| Filtration Rating In Microns: |
| 3.0 |
| Distance Between Mounting Hole Centers: |
| 3.190 inches |
| Design Type: |
| Reusable |
| Tempurature Rating: |
| Between -40.0 degrees fahrenheit and 225.0 degrees fahrenheit |
| Features Provided: |
| By-pass valve |
| Filtering Element Quantity: |
| 1 |
| Mounting Facility Thread Series Designator: |
| Unc |
| Maximum Operating Pressure: |
| 100.0 pounds per square inch |
| Filtering Media Design: |
| Pleated single filtering media response |
| First Intake Connection Type: |
| Threaded internal tube head side |
| Mounting Facility Thread Size: |
| 0.375 inches |
| First Discharge Connection Relationship To Intake Connection: |
| Identical to first intake connection |
| First Intake Thread Series Designator: |
| Un |
| First Intake Thread Size: |
| 1.875 inches |
| First Intake Thready Qty Per Inch (tpi): |
| 12 |
| First Intake Thread Class: |
| 2b |
| First Intake Thread Direction: |

Right-hand

NSN 4330-01-313-2178

Fluid Filter - Page 2 of 2

No Fiig: A24000



| Filtering System For Which Designed: |
|---|
| Full flow or by-pass flow |
| Special Features: |
| 25 psi bypass valve; pressure guage at location c on head; spin-on type element |
| Material: |
| Steel container/cartridge |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon |
| Surface Treatment: |
| Zinc container/cartridge |
| Style Designator: |
| Unthreaded shell |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| |