

View Online at <https://aerobasegroup.com/nsn/4330-01-317-2022>

**Mounting Type:**

Unthreaded hole head side

**Mounting Hole Diameter:**

0.270 inches

**Mounting Hole Quantity:**

2

**Body Length:**

2.900 inches

**Body Outside Diameter:**

4.090 inches

**Body Height:**

5.650 inches

**Filtration Rating In Microns:**

3.0 absolute

**Drop Pressure:**

19.0 pounds per square inch

**Differential Pressure:**

50.0 pounds per square inch

**Distance Between Mounting Hole Centers:**

3.120 inches

**Design Type:**

Reusable

**Temperature Rating:**

Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit

**Features Provided:**

By-pass valve and differential pressure indicator and thermal lockout

**Filtering Element Quantity:**

1

**Maximum Operating Pressure:**

150.0 pounds per square inch

**Filtering Media Design:**

Pleated single filtering media response

**First Intake Connection Type:**

Threaded internal tube head side

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**First Intake Thread Series Designator:**

Un

**First Intake Thread Size:**

1.062 inches

**First Intake Thready Qty Per Inch (tpi):**

12

**First Intake Thread Class:**

3b

**First Intake Thread Direction:**

Right-hand

**Filtering System For Which Designed:**

Full flow or by-pass flow

**Special Features:**

Visual indicator w/manual reset

**Material:**

Aluminum bodyfiber synthetic filtering medium and resin synthetic filtering mediumrubber buna n sealaluminum sediment bowl

**Media For Which Designed:**

Fuel/oil, hydrocarbon

**Style Designator:**

High pressure threaded body

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A24000